

# CIRCULATION UNIT

## FIXED TEMPERATURE, SERIES GFxX00



GFA311

GFA211

GFA212

GFF111

### PRODUCT DESCRIPTION

The mixing groups are used for the temperature control, mixing function, in the heating systems. This means that the heating water prepared in the heating source is mixed down to the desired set temperature, which then is delivered to the heating receiver, e.g. underfloor heating.

The units GFxX00 are equipped with thermostatic mixing valves. The temperature control, mixing function, is performed without power supply to the valve, and the desired mixed temperature is set on the valve itself. The series GFxX00 are constant temperature units, which means that just the mixing temperature can be affected, and the indoor temperature is a result of the temperature settings on the valve. The groups are used in systems without controllers but still with a need of temperature control, systems where indoor temperature, comfort is not requested to be high. The series GFxX00 are often used in systems with controllers which cannot be upgraded and provide an easy solution for additional heating circuit which require temperature control, mixing function.

Products are equipped with two shut-off valves with colour coded thermometers, one check valve placed on the return from the heating circuit and a insulation shell. All units are equipped with thermostatic mixing valves which are responsible for the constant temperature control.

When designing the circulation unit product line ESBE focused on performance, design, user friendly usage and environment. This applies to everything from manufacturing, materials to packaging.

### VERSIONS

ESBE direct supply circulation units are available in three different version; standard design with and without pump, and a compact design for areas with limited space.

### SERIES GFA200

The ESBE series GFA200 is a fixed temperature circulation unit equipped with a pump and a thermostatic mixing valve with temperature range 20-55°C. The series comes in two sizes; DN25 with kvs 4,5 and DN32 with kvs 4,8, with the ability of pump choice, Wilo or Grundfos. The pumps can be set to constant speed, variable pressure or constant pressure. The Grundfos pumps come with AutoADAPT feature which adjust the available pump pressure and the flow to the current system requirements.

The compact design of the unit has been thought through and focus put on components such as pump resulted in high performance of the circulation unit.

### SERIES GFA300

The ESBE series GFA300 is a compact but powerful fixed temperature circulation unit designed for applications where space matters, however there is no room for compromises. The GFA300 is a DN20 circulation pump with performance equals the corresponding DN25 groups. This is possible by adjusting the pump curves and consider the pressure losses in the group. By putting focus on performance, we achieved the smallest circulation unit with unique pump curves which are covering low and high demands.

The series GFA300 is equipped with a thermostatic mixing valve with kvs 3,4 and temperature range 20-55°C and with a Wilo pump which can be set to variable and constant pressure, and iPWM1/2.

### SERIES GFF100

The ESBE series GFF100 is a fixed temperature circulation unit, available in size DN25, designed to be used with almost any 180mm pump available on the market. The group is equipped with an insulation shell which can be adjusted according to the pump design, even if the pump is delivered with its own insulation. ESBE have put a lot of effort to make the adjustment process easy and clear, and to make the result of product adjustment like factory assembled.

The series GFF100 is equipped with a thermostatic mixing valve with kvs 3,4 and temperature range 20-55°C.

### SERVICE AND MAINTENANCE

The circulation unit does not require any specific maintenance under normal conditions.

### KEY BENEFITS

- High class insulation of hydronic parts
- Compact design
- Pre tested and ready to use
- Ready for 180mm pumps - applies to GFF100
- Adjustable insulation shell - applies to GFF100
- Symmetric design for left/right pump placement
- Designed to last and perform
- High-end product finish

&gt;&gt;&gt;

# CIRCULATION UNIT

## FIXED TEMPERATURE, SERIES GFxX00

### RELATED ACCESSORIES

#### ESBE Manifold

Manifolds for Series GFF100 and GFA200. See separate data sheet for further detailed information.

Manifolds for 1, 2, or 3 circulation units with integrated hydraulic separation.

Art. No.

66001100 \_\_\_\_\_ GMA411- for 1 unit

66001600 \_\_\_\_\_ GMA521 - for 2 units

66001700 \_\_\_\_\_ GMA531 - for 3 units

Manifold for 2, 3, 4 or 5 circulation units without integrated hydraulic separation function.

Art. No.

66001200 \_\_\_\_\_ GMA421- for 2 units

66001300 \_\_\_\_\_ GMA431 - for 3 units

66001400 \_\_\_\_\_ GMA441 - for 4 units

66001500 \_\_\_\_\_ GMA451 - for 5 units

Manifold for Series GFA300 without integrated hydraulic separation function. See separate data sheet for further detailed information.


Art. No.

66000500 \_\_\_\_\_ GMA321- for 2 units


66000600 \_\_\_\_\_ GMA331 - for 3 units

# CIRCULATION UNIT

## FIXED TEMPERATURE, SERIES GFxX00




GFA211



GFA212

### SERIES GFA200

Art. No.	Reference	DN	Pump	Temperature range	Connections		A	Weight [kg]	Replaces
					I	J			
61021100	GFA211	25	Wilo PARA 25/6	20-55 °C	G 1"	G 1½"	146	5,6	61020100
61021200		32	Wilo PARA 25/8		G 1¼"	G 1½"	157	5,9	61020200
61021300	GFA212	25	Grundfos UPM3 AUTO 25-50	20-55 °C	G 1"	G 1½"	141	5,7	61020300
61021400		32	Grundfos UPM3 AUTO 25-70		G 1¼"	G 1½"	141	5,8	61020400




GFA311

### SERIES GFA300

Art. No.	Reference	DN	Pump	Temperature range	Connections		Weight [kg]	Replaces
					I	J		
61023200	GFA311	20	Wilo PARA STG 15/8	20-55 °C	G ¾"	G 1"	4,0	61023100

# CIRCULATION UNIT

## FIXED TEMPERATURE, SERIES GFxX00




GFF111

### SERIES GFF100

Art. No.	Reference	DN	Temperature range	Connections		Weight [kg]	Note
				I	J		
61220100	GFF111	25	20-55 °C	G 1"	G 1½"	3,2	

### DIMENSIONING, CIRCULATION UNIT CHARACTERISTICS - PRESSURE LOSSES GFF111



# CIRCULATION UNIT

## FIXED TEMPERATURE, SERIES GFxXOO

**TECHNICAL DATA**



Visit [esbe.eu](http://esbe.eu) for further detailed information.

**The Circulation unit, in general**

Pressure class: \_\_\_\_\_ PN 10  
 Working pressure: \_\_\_\_\_ 1,0 MPa (10 bar)  
 Connections, \_\_\_\_\_ Internal thread (G), ISO 228/1  
 \_\_\_\_\_ External thread (G), ISO 228/1  
 Insulation: \_\_\_\_\_ EPP λ 0,036 W/mK

Media: \_\_\_\_\_ Heating water (in accordance with VDI2035)  
 \_\_\_\_\_ Water / Glycol mixtures, max. 50%.  
 Water / glycol mixtures are affecting the pump performance. In case of Applications where water / glycol mixtures are used, pump performance should be considered.

**Series GFA211**

Media temperature: \_\_\_\_\_ max. +100°C  
 \_\_\_\_\_ min. +5°C  
 Ambient temperature: \_\_\_\_\_ max. +58°C  
 \_\_\_\_\_ min. 0°C  
 Pump type, DN25: \_\_\_\_\_ Wilo PARA 25-130/6-43/SC  
 DN32: \_\_\_\_\_ Wilo PARA 25-130/8-75/SC  
 Power supply: \_\_\_\_\_ 230 ± 10% V AC, 50/60 Hz  
 Power consumption - Wilo PARA 25/6: \_\_\_\_\_ 3-43 W  
 - Wilo PARA 25/8 \_\_\_\_\_ 10-75 W  
 Enclosure rating: \_\_\_\_\_ IP X4D  
 Insulation class: \_\_\_\_\_ F  
 EEI (Energy Efficiency Index) - Wilo PARA 25/6: \_\_\_\_\_ <0,20  
 - Wilo PARA 25/8: \_\_\_\_\_ <0,21

Valve type: \_\_\_\_\_ Thermostatic mixing valve VTA572  
 Max. differential pressure drop: \_\_\_\_\_ 100kPa (1bar)  
 Temperature range: \_\_\_\_\_ 20-55°C  
 Temperature stability: \_\_\_\_\_ ±3°C\*

\* Valid at unchanged hot/cold water pressure, minimum flow rate 9 l/min. Minimum temperature difference between hot water inlet and mixed water outlet 10°C.

**Material, in contact with water**

Components: \_\_\_\_\_ Brass, Cast iron, Steel  
 Sealing material: \_\_\_\_\_ PTFE, Aramid fibre, EPDM

**Conformities and certificates**

CE LVD 2014/35/EU ErP 2015  
 EMC 2014/30/EU  
 RoHS3 2015/863/EU EnEV 2014  
 PED 2014/68/EU, article 4.3

**Series GFA212**

Media temperature: \_\_\_\_\_ max. +100°C  
 \_\_\_\_\_ min. +5°C  
 Ambient temperature: \_\_\_\_\_ max. +70°C  
 \_\_\_\_\_ min. 0°C  
 Pump type, DN25: \_\_\_\_\_ Grundfos UPM3 AUTO 25-50 130  
 DN32: \_\_\_\_\_ Grundfos UPM3 AUTO 25-70 130  
 Power supply: \_\_\_\_\_ 230 ± 10% V AC, 50/60 Hz  
 Power consumption - Grundfos UPM3 AUTO 25-50: 4-33 W  
 - Grundfos UPM3 AUTO 25-70 2-52 W  
 Enclosure rating: \_\_\_\_\_ IP 44  
 Insulation class: \_\_\_\_\_ N/A  
 EEI (Energy Efficiency Index): \_\_\_\_\_ <0,20

Valve type: \_\_\_\_\_ Thermostatic mixing valve VTA572  
 Max. differential pressure drop: \_\_\_\_\_ 100kPa (1bar)  
 Temperature range: \_\_\_\_\_ 20-55°C  
 Temperature stability: \_\_\_\_\_ ±3°C\*

\* Valid at unchanged hot/cold water pressure, minimum flow rate 9 l/min. Minimum temperature difference between hot water inlet and mixed water outlet 10°C.

**Material, in contact with water**

Components: \_\_\_\_\_ Brass, Cast iron, Steel  
 Sealing material: \_\_\_\_\_ PTFE, Aramid fibre, EPDM

**Conformities and certificates**

CE LVD 2014/35/EU ErP 2015  
 EMC 2014/30/EU  
 RoHS3 2015/863/EU EnEV 2014  
 PED 2014/68/EU, article 4.3

# CIRCULATION UNIT

## FIXED TEMPERATURE, SERIES GFxX00

### TECHNICAL DATA



Visit [esbe.eu](http://esbe.eu) for further detailed information.

#### Series GFA300

Media temperature: \_\_\_\_\_ max. +100°C  
 \_\_\_\_\_ min. +5°C  
 Ambient temperature: \_\_\_\_\_ max. +58°C  
 \_\_\_\_\_ min. 0°C  
 Pump type, DN20: \_\_\_\_\_ Wilo PARA STG 15-130/8-60/0  
 Power supply: \_\_\_\_\_ 230 ± 10% V AC, 50/60 Hz  
 Power consumption: \_\_\_\_\_ 2-60 W  
 Enclosure rating: \_\_\_\_\_ IP X4D  
 Insulation class: \_\_\_\_\_ F  
 EEI (Energy Efficiency Index): \_\_\_\_\_ <0,20

Valve type: \_\_\_\_\_ Thermostatic mixing valve VTA378  
 Max. differential pressure drop: \_\_\_\_\_ 100kPa (1 bar)  
 Temperature range: \_\_\_\_\_ 20-55°C  
 Temperature stability: \_\_\_\_\_ ±3°C\*

\* Valid at unchanged hot/cold water pressure, minimum flow rate 9 l/min.  
 Minimum temperature difference between hot water inlet and mixed water outlet 10°C.

#### Material, in contact with water

Components: \_\_\_\_\_ Brass, Cast iron, Steel  
 Sealing material: \_\_\_\_\_ PTFE, Aramid fibre, EPDM

#### Conformities and certificates

LVD 2014/35/EU    
 ErP 2015    
 EAC UK  
 EMC 2014/30/EU    
 ErEV 2014  
 RoHS3 2015/863/EU    
 PED 2014/68/EU, article 4.3

#### Series GFF100

Media temperature: \_\_\_\_\_ max. +100°C\*  
 \_\_\_\_\_ min. +5°C\*  
 Ambient temperature: \_\_\_\_\_ max. +60°C\*  
 \_\_\_\_\_ min. 0°C\*  
 \* consider data for choosen pump  
 Pump type: \_\_\_\_\_ N/A  
 Valve type: \_\_\_\_\_ Thermostatic mixing valve VTA372  
 Max. differential pressure drop: \_\_\_\_\_ 100kPa (1 bar)  
 Temperature range: \_\_\_\_\_ 20-55°C  
 Temperature stability: \_\_\_\_\_ ±3°C\*

\* Valid at unchanged hot/cold water pressure, minimum flow rate 9 l/min.  
 Minimum temperature difference between hot water inlet and mixed water outlet 10°C.

#### Material, in contact with water

Components: \_\_\_\_\_ Brass, Steel  
 Sealing material: \_\_\_\_\_ PTFE, Aramid fibre, EPDM

#### Conformities and certificates

PED 2014/68/EU, article 4.3    
 EAC UK  
 ErEV2014

### WIRING

Please see the Installation Instruction

# CIRCULATION UNIT


## FIXED TEMPERATURE, SERIES GFxX00

### DIMENSIONING, PUMP CAPACITY DIAGRAM


**Example:** Start with the heat demand of the heating circuit (e.g. 25 kW) and move horizontally to the right in the diagram to the  $\Delta t = 20^\circ\text{C}$  (temperature difference between flow and return of the heating circuit). Next go up and find the possible duty points.

Setting I gives duty point A with a residual head of 40 kPa for DN32. Setting II and III gives duty point B with a residual head of 45 kPa for DN32.


#### SERIES GFA211 – Constant differential pressure, Wilo pump



#### SERIES GFA211 – Variable differential pressure, Wilo pump



#### SERIES GFA211 – Constant speed, Wilo pump



# CIRCULATION UNIT


## FIXED TEMPERATURE, SERIES GFxX00

### DIMENSIONING, PUMP CAPACITY DIAGRAM


**Example:** Start with the heat demand of the heating circuit (e.g. 25 kW) and move horizontally to the right in the diagram to the  $\Delta t = 20^\circ\text{C}$  (temperature difference between flow and return of the heating circuit). Next go up and find the possible duty points.

Setting I gives duty point A with a residual head of 15 kPa for DN32. Setting II and III gives duty point B with a residual head of 28 kPa for DN32.


#### SERIES GFA212 - Constant differential pressure, Grundfos pump



#### SERIES GFA212 - Variable differential pressure, Grundfos pump



#### SERIES GFA212 - Constant speed, Grundfos pump



# CIRCULATION UNIT


## FIXED TEMPERATURE, SERIES GFxX00

### DIMENSIONING, PUMP CAPACITY DIAGRAM


**Example:** Start with the heat demand of the heating circuit (e.g. 20 kW) and move horizontally to the right in the diagram to the chosen  $\Delta t$ , which is the temperature difference between flow and return of the heating circuit (e.g. 20°C). Next go up and find the possible duty points.

Setting I gives duty point A with a residual head of 18 kPa for DN32. Setting II gives duty point B with a residual head of 32 kPa and III gives duty point C with a residual head of 38 kPa for DN32.


#### SERIES GFA311 - Constant differential pressure, Wilo pump



#### SERIES GFA311 - Variable differential pressure, Wilo pump



#### SERIES GFA311 - Ext iPWM 1/ iPWM 2, Wilo pump




# CIRCULATION UNIT

## FIXED TEMPERATURE, SERIES GFxX00

### INSTALLATION EXAMPLES

①



The primary function of the thermostatic mixing unit (GFx) is flow temperature control, mixing function. The Series GFx of circulation units are used in systems where the heating source is not equipped with a controller or a controller with limited functions. The circulation units series GFx are the perfect choice for applications where mixing function is required and temperature comfort is not the highest priority.

*The shown applications are only examples of product use!  
Before using the product in any application, the regional and national regulations need to be checked.*